MOTOR SPECS/PERFORMANCE DATA	
MODEL NUMBER	YXN5664
HP	1.0
VOLT	208-230/460
PHASE	3
HZ	60
RATED SPEED	1740 RPM
FLA (@460VOLTS)	1.5 AMPS
FRAME	56C
ENCLOSURE	TEFC
IP RATING	55
INS CLASS	F
EFFICIENCY	83%
POWER FACTOR	.78
FULL LOAD TORQUE	4.1 Nm (3.02 ft-Lbs)
MAX TORQUE	17 Nm (12.5 ft-Lbs)
START AMPERAGE	13 Amps
SERVICE FACTOR	1.15
RATING @	40 °C AMBIENT
USABLE AMPS @208V	2.80
LOCKED ROTOR CODE	L
NEMA DESIGN CODE	B
LR KVA CODE	L
NO LOAD CURRENT	0.90 AMPS
LINE-LINE RESIST@25C	12 OHMS
TEMP RISE C@FL	40°C
LOCKED ROTOR TORQ	14 Nm (10.33 ft-lbs)
TEMP RISE @SF LOAD	50°C
SHIPPING WEIGHT (LBS)	43
DUTY	CONTINUOUS

REVISIONS					
REV	ECO. NO.	DESCRIPTION	DWN/DATE	CHK/DATE	APVD/DATE
A	XX	RELEASE FOR WEBSITE	P.S.K. 04/28/10		



SECTION A-A



WIRING DIAGRAM



NOTE: TO REVERSE ROTATION, INTERCHANGE ANY TWO LEADS

NOTES:

3. INTERPRET ABBREVIATIONS PER ANSI Y1.1.
2. INTERPRET DIMENSIONS AND TOLERANCES PER ANSI Y14.5M.
1. INTERPRET DRAWING PER ANSI Y14.3.

NOTICE: CONFIDENTIAL INFORMATION
THIS DOCUMENT IS THE PROPERTY OF SMC AND SHALL NOT BE COPIED, REPRODUCED OR USED AS THE BASIS FOR SALE OR MANUFACTURE OF APPARATUS OR DEVICES WITHOUT WRITTEN PERMISSION.

APPLICABLE SPECIFICATIONS	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS TOLERANCES	APPROVALS / SIGNATURE / DATE	SMC North America
		DRAWN BY: Phillip Keller 11/10/09	MOTOR, 1 HP, SS, 3 PH, 56C, YXN5664
		CHECKED BY:	SIZE D | PART NO. 002847-01 | DRAWING NO. 002847-01 | REV A
MATERIAL N/A		APPROVED BY:	SCALE 1/1 | DO NOT SCALE DRAWING | SHEET 1 OF 1
PROTECTIVE/DECORATIVE FINISH N/A		FILENAME: WS002847-01DA	